



ENOVIA DESIGNSYNC MODULES COMMAND QUICK REFERENCE

add - Adds new objects to a module

```
add [-[no]candidates] [-filter <string>] [-modulecontext <workspace>]
[-[no]recursive [-[no]emptydirs]]
[-report {error | brief | normal | verbose}] [-no[selected]] [--]
<workspace module> <argument> [<argument>...]
```

addhref - Creates a hierarchical reference between modules

```
addhref <fromargument> <toargument> [-name <name>]
[-relpath <rel_path>] [-selector] [-rootpath <path>]
```

```
addhref <fromargument> [-file <filename>] [-tcllist
<toargument_specification_list>] [-relpath <rel_path>] [-rootpath <path>]
```

```
addhref [-selector] [--] <fromargument> <toargument>
[<toargument>...]
```

cancel - Cancels a previous checkout operation

```
cancel [-exclude <object>[,<object>...]] [-filter <string>]
[-[no]force] [-hreffilter <string>]
[-keep | -share | -reference] [-modulecontext <context>]
[-[no]selected] [-[no]retain] [-trigarg <arg>] [--] [<argument>
<argument>...]]
```

ci - Checks in the specified objects

```
ci [-autohrefversions | -[no]hrefversions]
[-branch <branch> | -branch auto(<branch>)]
[-[no]comment "<text>" | -cfile <file>] [-datatype ascii | binary]
[-[no]dryrun] [-exclude <object>[,<object>...]] [-filter <string>]
[-[no]force] [-hreffilter <string>] [-[no]iflock]
[-keep [-keys <mode>] | -lock [-keys <mode>] | -share | -reference]
[-modulecontext <context>] [-[no]new]
[-[no]recursive] [-report {error | brief | normal | verbose}]
```

```
[-[no]resume] [-[no]retain] [-[no]retry] [-[no]selected]
[-[no]skip] [-tag <tagname>] [-trigarg <arg>] [--] [<argument>
<argument>...]]
```

compare - Compares two defined sets of files or objects

```
compare [-format list|text]
[-exclude <string>] [-filter <string>] [-hreffilter <string>]
[-modulecontext <context>] [-output <file> | -stream <stream>] [-[no]path | -fullpath]
[-[no]recursive] [-report <mode>[+<mode>]-<mode>]]
[-[no]selected] [-[no]versionable] [-workspace | -vault]
[-writableunlocked] [-xtras <xtras>] [--] [<argument>
<argument>...]]
```

```
[-report silent|brief|normal|verbose] [-[no]same]
[-selector <selector> [-hrefmode dynamic|static|normal]]
[-selector2 <selector2> [-hrefmode2 dynamic|static|normal]]
```

```
[-view <viewName>[,<ViewName>,...]] [--] [<argument> [<argument>]]
```

contents - Lists the contents of a configuration or a module

```
contents [-exclude <object> [,<object>...]] [-filter <string>]
[-format <text>|list] [-fullpath] [-hreffilter <string>]
[-hrefmode <dynamic|static|normal>]
[-modulecontext <context>] [-output <file>] [stream <stream>]
[-[no]path] [-[no]recursive]
[-report {silent | brief | normal | verbose}]
[-selector <selector>] [-[no]versions]
[-view view1[,view2,...]] [--] [<argument>]
```

diff - Compares files and versions of files

```
diff [-ancestor <commonAncestorFile>] [-binary] [-case] [-embed]
[-kk] [-member <cellview_path>] [-modulecontext <context>]
[-standard | -unified | -synccdiff | -annotate | -gui]
[-output <resultFile>] [-[no]usemoduleversions] [-version <id>]
[-white]{[-file1] <fileA>} {[<file2>] <fileB>} [--]
```

edithrefs - Updates the hierarchical references for a module

```
edithrefs [-infile <file-containing-href-edits> | -outfile <file-to-write-hrefs-to>]
[-report brief|normal|verbose] [--] [<argument>]
```

lock - Creates a server-side lock on a module branch

```
lock [-[no]comment [<string>] [--] [<argument>]
```

ls - Lists information about the specified objects

```
ls [-[no]addselect] [-[un]changed] [-exclude <string>]
[-filter <string>] [-format list | text] [-[no]header]
```

```
[-hreffilter <string>] [-[un]locked] [-[un]modified]
[-modulecontext <context>] [-[no]needsmerge] [-branch <branch>]
[-merged added|rename|remove|all|""]
[-output <file> | -stream <stream>] [-[no]path | -fullpath]
[-[no]recursive] [-report <mode>[+<mode>]-<mode>]
[-[no]selected] [-[no]versionable] [-workspace | -vault]
[-writableunlocked] [-xtras <xtras>] [--] [<argument>
<argument>...]]
```

mkbranch - Creates a new branch

```
mkbranch [-[no]comment <text>] [-exclude <string>,[<string>...]]
[-[no]selected] [-version <selector>] [--]
<branchname> [<argument> [<argument> ...]]
```

mkfolder - Creates a folder (directory)

```
mkfolder [--] <foldername> [<foldername>...]
```

mkmod - Creates a module on a server

```
mkmod [-checkin [-[no]retry]] [-[no]comment "<text>"] [-filter
<string>]
[-path <workspace_path>] [-report {error|brief|normal|verbose}]
<argument>
```

mvmember - Changes the natural path of a module member

```
mvmember [-[no]comment] [-[no]immediate] [-modulecontext <context>]
[-[no]selected] [--] [<fromargument>... ] <toargument>
```

populate - Fetches or updates specified objects

```
populate [-[no]connectinstances] [-[no]emptydirs]
[-exclude <object>[,<object>...]] [-filter <string>]
[-[no]force] [-full | -incremental] [-hreffilter <string>]
[-hrefmode {static | dynamic | normal}]
[[-lock [-keys <mode> | -from {local | vault}]] | -get [-keys <mode> | -from {local | vault}]]]
[-share] | [-reference] [-lock -reference] ]
[-log <filename>] [-mcachemode <mcache_mode>]
[-mcachepaths <path_list>] [-[no]merge]
[-modulecontext <context>] [-[no]new]
[[-overlay <selector>[,<selector>...]] | -version <selector>[,<selector>...]]] [-path <path>]
[-[no]recursive] [-[no]replace]
```

[-report {error|brief|normal|verbose}] [-[no]retain]
[-savelocal <value>] [-trigarg <arg>] [-[no]unifystate]
[-view view1[,view2,...]] [-xtras <list>] [--]
<argument> [<argument>...]
remove - Removes a module member from a module
remove [-[no]comment "<text>"] [-filter <string>] [-[no]force]
[-[no]immediate] [-[no]keep] [-modulecontext <context>]
[-[no]recursive] [--] <argument>
rmfile - Deletes the specified object
rmfile [-trigarg <arg>] [--] <object> [<object> [...]]
rmfolder - Deletes the specified folder
rmfolder [-[no]keepvid] <folder> [-[no]recursive] [-trigarg <arg>]
<folder> [...]
rmhref - Removes a hierarchical reference between modules
rmhref <fromargument> <toargument> [<toargument>...]
rmmod - Removes a module from a server or workspace
rmmod [-[no]force] [-[no]keep] [-[no]notes] [-[no]recursive]
[-report error|brief|normal|verbose] [-[no]unmanaged]
[-[no]vaultdata] [-xtras <string>] <argument>
setfilter - Sets the persistent filter or hreffilter list
setfilter [-filter | -hreffilter] [-[no]recursive] [--]
<workspace module> <filter>|<hreffilter>
setmirror - Maps a mirror directory to a working directory
setmirror [--] [<mirrorDirectory> <localWorkingDirectory>]
setroot - Sets the root workspace location
setroot -[un]set [--] <workspace folder>
setselector - Sets the persistent selector list
setselector [-recursive] [-selected] [--]
<selector>[,<selector>...] <argument> [argument>...]
setview - Associates a view with a work area
setview [-[no]recursive [--] <argument> <view>[,<view>...]
showrefs - Displays the hierarchy of a module
showrefs [-[no]conflicts] [-format text|list]
[-hrefmode {dynamic | static | normal}]
[no]overridden [-[no]recursive]

[-report {brief | normal | verbose | script}]
[-[no]stopatconflict] [-xtras <xtras>] <argument>
showmcache - Lists the modules in one or more module caches
showmcache [-format {text | list}] [-mcachepaths <path_list>]
showmods - Displays the modules available on a server or workspace
showmods [-[no]all] [-format [{text | list}]] [-filter <string>]
[-report {brief | normal | verbose | script}] [-[no]top]
<argument>
showstatus - Displays the status of a module in your workspace
showstatus [-format <type>] [-[no]hrefs] [-[no]objects]
[-[no]recursive] [-releases]
[-report {brief | normal | verbose | summary | script}]
[-xtras <xtras>] <argument>
tag - Assigns a tag to a version or a branch
tag [-branch <branch> | -branch auto(<branch>) | -[no]delete |
-[no]replace | -version <selector>] [-[no]comment <text>]
[-exclude <object>[,<object>...]] [-filter <object>[,<object>]]
[-modulecontext <context>] [-[im]mutable] [-[no]recursive]
[-report <mode>] [-[no]selected] [-trigarg <arg>] [-warn <mode>]
[-xtras <xtras>] [--] <tagname> [<argument> [<argument> ...]]
unlock - Releases the lock on the specified object(s)
unlock [-branch <branch>] [-exclude <object>[,<object>...]]
[-modulecontext <context>] [-[no]recursive]
[-[no]selected] [-trigarg <arg>] [--]
<argument> [<argument> ...]
vhistory - Displays an object's version history
vhistory [-branch <branchname> -descendants <n> |
-lastversions <n> -lastbranches <n> | -all]
[-exclude <string>] [-format list | text] [-maxtags <n>]
[-modulecontext <context>]
[-output <filename> | -stream <port>] [-report <mode>]
[-[no]selected] [-xtras <list>] [--] <argument>
<argument>...
webhelp - Launches Graphical Web Browser to view help
webhelp [-mode module|file|all] [<topic> ...]

swap replace - Replaces the version of a workspace module
swap replace [-force] [-hrefmode {static|normal|dynamic}]
[-mcachemode {link|server}] [-mcachepaths <path>[<path>...]]
[-trigarg <arg>] [-report {error|brief|normal|verbose}]
[-xtras <>] [--] <selector> <argument>
swap restore - Restores a previously swapped module version
swap restore [-[no]force] [-mcachemode {link|server}]
[-mcachepaths <path>[<path>...]]
[-report {error|brief|normal|verbose}]
[-parent <parent_module_inst>] [-trigarg <arg>]
[-xtras <string>] [--] <argument>
swap show - Shows the workspace's currently swapped modules
swap show [-format {text|list}] [-report {brief|normal|verbose}] [--]
<argument>
whereused member - Lists module versions containing a module member
whereused member [-format list|text] [-modulecontext
<moduleVersionURL>]
[-report brief|normal|verbose]
[-showtags all|none|immutable|version|member]
[-versions <selector>,...] <argument>
whereused module - Traces the use of hierarchical references
whereused module [-format list|text] [-[no]recursive] [-report
<mode>]
[-showtags all|none|immutable|version]
[-versions <selector>,...] <argument>
whereused vault - Traces the use of hierarchical references
whereused vault [-format list|text] [-[no]recursive] [-report <mode>]
[-showtags all|none|immutable|version]
[-versions <selector>,...] <argument>

3DEXPERIENCE 2022x. Copyright © Dassault Systemes. All rights reserved.